



AK Rubber & Industrial Supplies Ltd

SHEETING • MATTING • GASKETS • STRIP • MOULDINGS
EXTRUSIONS • INDUSTRIAL HOSES • FITTINGS • CLIPS • SEALANTS



18 Twyford Business Centre • London Road • Bishop's Stortford • Herts • CM23 3YT
email: sales@akrubber.co.uk Tel: 01279 719000 Fax: 01279 719001

COMMERCIAL RUBBER – PRODUCT DATA

Grade	Polymer	Colour	Hardness Shore 'A'	Density (g/cm ³)	Tensile Strength (MPa)	Elongation At Break (%)	Temperature Range (°C)	Description
AKM110	SBR	Black	70°	1.60	2.5	130	-20°C to +70°C	Hard Commercial
AKM123	SBR	Black	70°	1.50	3.0	150	-20°C to +70°C	Hard Commercial
AK8313	NR/SBR	Black	65° ± 5°	1.50 ± 5%	3.0	250 (Min)	-30°C to +70°C	Hard Commercial
AKN02	NR/SBR	Black	65° ± 5°	1.55 ± 5%	3.5	300 (Min)	-20°C to +70°C	Hard Commercial
AKN02E	NR/SBR	Black	65° ± 5°	1.50 ± 5%	2.5	200 (Min)	-20°C to +70°C	Economy Commercial
AK8172P/F	NR/SBR	Black	65° ± 5°	1.50 ± 5%	3.0	250 (Min)	-30°C to +70°C	Commercial Insertion
AK8172C/M	NR/SBR	Black	65° ± 5°	1.50 ± 5%	3.0	250 (Min)	-30°C to +70°C	Commercial Insertion – Cloth Marked
AKN66	NR/SBR	Black	65° ± 5°	1.50 ± 5%	3.5	300 (Min)	-20°C to +70°C	Commercial Insertion

Standard Roll Sizes:-

Thickness	Width	Length
1.0mm	1400mm	10 Metres
1.5mm	1400mm	10 Metres
2.0mm	1400mm	10 Metres
3.0mm	1400mm	10 Metres
4.0mm	1400mm	10 Metres
5.0mm	1400mm	10 Metres
6.0mm	1400mm	10 Metres

Thickness	Width	Length
8.0mm	1400mm	10 Metres
10.0mm	1400mm	10 Metres
12.0mm	1400mm	5 Metres
15.0mm	1400mm	5 Metres
20.0mm	1400mm	5 Metres
25.0mm	1400mm	5 Metres

IN EACH CASE CUT LENGTHS, PARTS OR STRIP
CAN BE SUPPLIED – PLEASE ENQUIRE

WE CAN ALSO OFFER THESE MATERIALS
WITH A SELF-ADHESIVE BACKING