



AK Rubber & Industrial Supplies Ltd

SHEETING • MATTING • GASKETS • STRIP • MOULDINGS
EXTRUSIONS • INDUSTRIAL HOSES • FITTINGS • CLIPS • SEALANTS



18 Twyford Business Centre • London Road • Bishop's Stortford • Herts • CM23 3YT
email: sales@akrubber.co.uk Tel: 01279 719000 Fax: 01279 719001

ABRASION RESISTANT & SHOTBLAST RUBBER – PRODUCT DATA

Grade	Polymer	Colour	Hardness Shore 'A'	Density (g/cm ³)	Tensile Strength (MPa)	Elongation At Break (%)	Abrasion Resistance (mm ³)	Temperature Range (°C)	Description
AKN06	NR	Tan	45°	1.04	16	600	Excellent	-30°C to +70°C	Tan Para Rubber
AKM134	NR	Tan	40°	1.02	16	600	120	-20°C to +70°C	Tan Para Rubber
AK1062	NR/SBR	Tan	40°	1.05	17	750	Excellent	-30°C to +70°C	Tan Shotblast
AKM150	NR/SBR	Tan	45°	1.2	10	400	150	-20°C to +70°C	Tan Shotblast Economy
AKN04	NR/SBR	Black	60°	1.2	14	500		-30°C to +70°C	Black Shotblast
AKM151	NR/SBR	Black	60°	1.15	15	450	120	-20°C to +70°C	High Abrasion
AKM1310	NR	Black	50°	1.2	8	400	140	-20°C to +70°C	Black Shotblast

Standard Roll Sizes:-

Thickness	Width	Length
1.0mm	1400mm	10 Metres
1.5mm	1400mm	10 Metres
2.0mm	1400mm	10 Metres
3.0mm	1400mm	10 Metres
4.0mm	1400mm	10 Metres
5.0mm	1400mm	10 Metres
6.0mm	1400mm	10 Metres

Thickness	Width	Length
8.0mm	1400mm	10 Metres
10.0mm	1400mm	10 Metres
12.0mm	1400mm	5 Metres
15.0mm	1400mm	5 Metres
20.0mm	1400mm	5 Metres
25.0mm	1400mm	5 Metres

IN EACH CASE CUT LENGTHS, PARTS OR STRIP CAN BE SUPPLIED – PLEASE ENQUIRE

WE CAN ALSO OFFER THESE MATERIALS WITH A SELF-ADHESIVE BACKING