



AK Rubber & Industrial Supplies Ltd

SHEETING • MATTING • GASKETS • STRIP • MOULDINGS
EXTRUSIONS • INDUSTRIAL HOSES • FITTINGS • CLIPS • SEALANTS



18 Twyford Business Centre • London Road • Bishop's Stortford • Herts • CM23 3YT
email: sales@akrubber.co.uk Tel: 01279 719000 Fax: 01279 719001

NEOPRENE RUBBER – PRODUCT DATA

Grade	Polymer	Colour	Hardness Shore 'A'	Density (g/cm ³)	Tensile Strength (MPa)	Elongation At Break (%)	Temperature Range (°C)	Description
AK1642	SBR/CR	Black	60° ± 5°	1.5 ± 0.05	3.0 Min	250	-20°C to +70°C	Commercial
AKC20	SBR/CR	Black	70°	1.4	5.0	200 min	-20°C to +110°C	Commercial
AKC20E	SBR/CR	Black	70°	1.4	4.0	250	-20°C to +110°C	Commercial Economy
AKM132	SBR/CR	Black	50°	1,25	6.0	300	-20°C to +90°C	Soft Commercial
AKM133	SBR/CR	Black	60°	1.3	5.0	300	-20°C to +90°C	Medium Commercial
						350		
AKC66	SBR/CR	Black	70°	1.4	6.0	350	-20°C to +110°C	Commercial Insertion
AK1641/1P	SBR/CR	Black	60° ± 5°	1.5 ± 0.05	3.0 Min		-20°C to +70°C	Commercial Insertion

Standard Roll Sizes:-

Thickness	Width	Length
1.0mm	1400mm	10 Metres
1.5mm	1400mm	10 Metres
2.0mm	1400mm	10 Metres
3.0mm	1400mm	10 Metres
4.0mm	1400mm	10 Metres
5.0mm	1400mm	10 Metres
6.0mm	1400mm	10 Metres

Thickness	Width	Length
8.0mm	1400mm	10 Metres
10.0mm	1400mm	10 Metres
12.0mm	1400mm	5 Metres
15.0mm	1400mm	5 Metres
20.0mm	1400mm	5 Metres
25.0mm	1400mm	5 Metres

IN EACH CASE CUT LENGTHS, PARTS OR STRIP
CAN BE SUPPLIED – PLEASE ENQUIRE

WE CAN ALSO OFFER THESE MATERIALS
WITH A SELF-ADHESIVE BACKING